



Wear is unlimited...

"Jyoti Cero Products" brings it within limit

**MOTTO : INNOVATE TO PROTECT** <sup>TM</sup>

## Track Pad

A Track Pad, also called Groove Rubber Pad, is installed between the rail tie plate and foot of the rail, made by a Special grade of Rubber to protect the sleeper top from wearing and impacting. It is used to reduce shock and vibration in the rail system with such upgraded load distribution. We manufactured this Grooved Rubber pad with special type of rubber composition to take the axial load minimum 42 ton and ambient temperature capacity is 100° C.

### Track Pad Features are as under

- Axial Load capacity is minimum 42 ton
- load distribution cover a larger surface area
- ambient temperature capacity is 100° C.
- Reducing load concentration and enhance the life
- Reducing noise and structural vibrations
- Sealing function between the top support and rail bottom



## Boltable Chutes

*(A new concept of designing)*

We came into the market with a new concept of designing of varies type of boltable chutes with different type of lining like -Rubber Liner PU Liner, Polymer Liner, Ceramic Embedded rubber Liner with MS back plate as per the requirement of working zone.

### Boltable Chutes Features are as under:

- 1). Easy to install
- 2). Replace the damage parts to open the bolts and fit a new one parts. No need to replace full chute.
- 2). Customer can keep the stock of only impact zone and replace it minimum time of shut down.



### M/s Jyoti Cero Rubber

NS-1(P) &2(P), Phase-III, Industrial Area, Adityapur, Jamshedpur-831013 • Phone : 0657-2370056 • Mobile : (0)9334800333, (0)9204750280, (0)9204750282, (0)9204750292, (0)9204750294 • Email : cerorubber@yahoo.com, info@jyoticerorubber.com • Website : www.jyoticerorubber.com